



Email: boatsales@warrenhaymarine.co.nz

Website: https://www.warrenhaymarine.co.nz/

211 Port Road Whangarei 0110



Lowrance Elite FS 9 with Active Imaging 3-in-1 Transducer (AUS/NZ)

\$2099.00 NZD







Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.



Phone: (09) 430 2666

Email: boatsales@warrenhaymarine.co.nz

Website: https://www.warrenhaymarine.co.nz/

211 Port Road Whangarei 0110

Specifications

Boat Details

Price \$2099.00 NZD Boat Brand Lowrance
Model Lowrance Elite FS9 Length 0.00

Year 2023 Category Boat Parts and Accessories

Hull Style Hull Type

Power Type Stock Number

Condition New State New Zealand

Suburb Whangarei Engine Make

Description

The new Elite™ Fishing System (FS) gives you access to the full line-up of Lowrance fishfinding tools – including ActiveTarget™ live sonar, Active Imaging™, FishReveal™ and preloaded C-MAP® Contour™ + charts – all at a more affordable price than other fishfinder/chart plotters in its category Overview The new Elite™ Fishing System (FS) gives you access to the full line-up of Lowrance fishfinding tools – including ActiveTarget™ live sonar, Active Imaging™, FishReveal™, and preloaded C-MAP® Contour™ + charts Key Features

- ActiveTarget Live sonar and Active Imaging compatible: Live Sonar: Supports sonar accessories such as ActiveTarget™ and Active Imaging™ 3-in-1 Sonar
- Full networking capability: Multiple Displays: Share sonar, charting, waypoints, and other user data between displays
- High-Resolution Multi-touch screen
- Preloaded with C-MAP Contour + charts (AMER,APAC)
- NMEA 2000®: Support and control NMEA 2000® devices
- Halo Radar: Drive Lowrance radar domes directly
- Total Control: Full touchscreen control of Power Pole® anchors and Ghost® Trolling Motor

Sonar

Power Output □□□Max 1 kW RMS

Sonar Connections ∏∏One connector for Active Imaging SideScan, DownScan and CHIRP

Active Imaging 3-in-1 □□□DownScan Imaging™ at 455 kHz: Max 300 ft / 91 m: SideScan Imaging at 455kHz: Max 300 ft / 91 m: SideScan Imaging at 455kHz: Max 300

ft./91 m to each side

CHIRP Sonar | | | High Range (160-240kHz)/200 kHz: 1000 ft / 305 m CHIRP Sonar | | Med Range (60-100kHz)/83 kHz: 1000 ft / 305 m CHIRP Sonar | | Low Range (40-60kHz)/50 kHz: 3000 ft / 900 m

Available Sonar Frequencies DDDLow/Mid/High CHIRP, 50/83/200 kHz Broadband, 455/800 kHz SideScan/DownScan

imaging

Depth Alarm || Yes

Shallow Alarm □□□Yes

Temperature Readings □□□Yes

Transducer Type [][]Single 9-pin Connection; Multiple Transducer Selections from Lowrance® and Airmar®

Environmental

Operating temperature range \(\Pi\Pi\-15\circ\) to +55\circ\ (5\circ\) to 131\circ\)

Storage temperature $\square\square\square$ -20°C to +60°C (4°F to 140°F)

Waterproof rating □□□IPX6 and IEXe7ctrical

Supply voltage □□□12 V DC (10 - 17 V DC min - max)

Recommended fuse rating [][] 3 A

Power consumption (maximum) □□□28 W (2 A at 13.8 V **D**S)play

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.



Phone: (09) 430 2666

Email: boatsales@warrenhaymarine.co.nz

Website: https://www.warrenhaymarine.co.nz/

211 Port Road Whangarei 0110

Resolution □□□800 x 480 pixels

Viewing angles in degrees □□□50° top, 60° bottom, 70° left and right

Brightness □□□> 1200 nits

Touch screen □□□MultitoBb\sical

Weight (display only) □□□1.2 kg (2.7 lbs.)

Compass Safe Distance □□□0.5 m (1.6Iftt\right)rface/Connectivity

NMEA 2000® [[]] port (Micro-C connector)

Data card reader $\square\square 1x$ slot (microSD, SDXC)

Ethernet □□□1 port, (5-pin Ethernet connector, 100Base-T)

Sonar □□□1 port (9-pin connector)

WiFI Internal □□□802.11b/g/n : No wireless networking between units

Bluetooth® □□□4.0 with support for Bluetooth® Classic

GPS [[[]]10Hz high speed update WAAS, MSAS, EGNOS, GLONASS

Disclaimer